

دوربین های IP

HIKVISION
Authorized Distributor



لیست قیمت دوربین ها و دستگاه های ضبط تصاویر تحت شبکه

OPTIX
IMAGING TECHNOLOGY

تهران، خیابان یوسف آباد، خیابان شهید جهان آرا، خیابان ۳۹، پلاک ۴۰

۰۲۱۸۸۳۵۲۷۲۴







www.agrintech.ir - www.optix.ir







- Network Camera**



DS-2CD2020F-I	DS-2CD2022WD-I	DS-2CD2042WD-I	DS-2CD2052-I
			
"1/3"" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, IR range: up to 30m, Bracket included, Housing: plastic and metallic, DC12V & external PoE	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, H.264+	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (6mm optional), IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, H.264+	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, H.264+ Optimized Codec
4,750,000 IRR	5,750,000 IRR	6,400,000 IRR	7,880,000 IRR



تهران، خیابان یوسف آباد، خیابان شهید جهان آرا، خیابان ۳۹، پلاک ۴۰
 ۰۲۱۸۸۳۵۲۷۲۴
www.agrintech.ir - www.optix.ir











DS-2CD2120F-I	DS-2CD2120F-IS	DS-2CD2122FWD-I
		
<p>"1/3"" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage</p>	<p>"1/3"" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included),-S: Audio/Alarm IO connectors</p>	<p>"1/3"" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6/8/12mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+ Optimized Codec</p>
4,750,000 IRR	5,160,000 IRR	5,750,000 IRR
DS-2CD2122FWD-IS	DS-2CD2142FWD-IS	DS-2CD2152F-IS
		
<p>"1/3"" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6/8/12mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+ Optimized Codec/ -S: Audio/Alarm IO</p>	<p>"1/3"" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+-S: Audio/Alarm IO"</p>	<p>"1/3"" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+-S: Audio/Alarm IO"</p>
6,160,000 IRR	6,700,000 IRR	8,300,000 IRR




DS-2CD2322WD-I	DS-2CD2342WD-I	DS-2CD2352-I
		
1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 4mm/F2.0 lens (2.8/6/8/12mm optional),H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m, H.264+ Optimized Codec	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m, H.264+	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 30m, H.264+
6,520,000 IRR	7,230,000 IRR	8,710,000 IRR
DS-2CD2420F-IW	DS-2CD2422FWD-IW	DS-2CD2442FWD-IW
		
"1/3"" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 10m, -W: Built-in Wi-Fi with WPS"	1/2.8" Progressive CMOS, ICR, ICR, 0.01lux/F1.2, 1920x1080: 25fps(P)/30fps(N), 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, built-in WIFI, H.264+	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream,DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to10m, built-in WIFI, H.264+ Optimized Codec.
4,750,000 IRR	5,870,000 IRR	6,520,000 IRR

DS-2CD2520F	DS-2CD2522FWD-I	DS-2CD2542FWD-IS
		
<p>1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board card slot (SD card not included), Vandal-proof IK10,</p>	<p>"1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), H.264+</p>	<p>"1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support onboard storage up to 128GB(SD card not included), H.264+-S: Audio/alarm IO</p>
<p>4,510,000 IRR</p>	<p>7,880,000 IRR</p>	<p>9,000,000 IRR</p>











تهران، خیابان یوسف آباد، خیابان شهید جهان آرا، خیابان ۳۹، پلاک ۴۰
 ۰۲۱۸۸۳۵۲۷۲۴
www.agrintech.ir - www.optix.ir




DS-2CD2620F-I	DS-2CD2620F-IZ	DS-2CD2622FWD-IS	DS-2CD2642FWD-IS	DS-2CD2642FWD-IZS
				
"1/3"" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/ MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included),	"1/3"" Progressive CMOS, ICR, 0lux with IR,1920x1080: 25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/ MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included),-Z:Motorized VF lens"	"1/2.8"" Progressive CMOS, ICR, 0.01lux/F1.2, 1920x1080: 25fps(P)/30fps(N), 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support onboard storage up to 64GB (SD card not included), H.264+ -S: Audio/alarm IO	"1/3"" Progressive CMOS, ICR, 0.01lux/F1.2,2688x1520: 20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 64GB (SD card not included), H.264+ -S: Audio/alarm IO	"1/3"" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 64GB (SD card not included), H.264+ -S: Audio/alarm IO/-Z: Motorized VF lens"
8,180,000 IRR	9,660,000 IRR	11,860,000 IRR	13,520,000 IRR	15,930,000 IRR
DS-2CD2652F-IS	DS-2CD2652F-IZS	DS-2CD2720F-I	DS-2CD2720F-IZ	DS-2CD2722FWD-IS
				
"1/3"" Progressive CMOS, ICR, 0.01lux/F1.2, 2560x1920:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), H.264+-S: Audio/alarm IO	"1/3"" Progressive CMOS, ICR, 0.01lux/F1.2,2560x1920:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), H.264+/-S:Audio /alarm IO/-Z: Motorized VF lens"	"1/3"" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/ MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof"	"1/3"" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/ MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof,-Z:Motorized VF lens"	"1/2.8"" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support onboard storage up to 128GB (SD card not included), Vandal-proof housing, H.264+ -S: Audio/alarm IO
16,700,000 IRR	18,740,000 IRR	8,470,000 IRR	9,830,000 IRR	12,110,000 IRR

DS-2CD2742FWD-IS	DS-2CD2742FWD-IZS	DS-2CD2752F-IS	DS-2CD2752F-IZS
			
<p>"1/3"" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+ -S: Audio/alarm IO</p>	<p>"1/3"" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+ -S: Audio/alarm IO/-Z: Motorized</p>	<p>"1/3"" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+ -S: Audio/alarm IO</p>	<p>"1/3"" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+ -S: Audio/alarm IO/-Z: Motorized VF lens"</p>
<p>13,770,000 IRR</p>	<p>16,190,000 IRR</p>	<p>17,090,000 IRR</p>	<p>19,000,000 IRR</p>



تهران، خیابان یوسف آباد، خیابان شهید جهان آرا، خیابان ۳۹، پلاک ۴۰
 ۰۲۱۸۸۳۵۲۷۲۴
www.agrintech.ir - www.optix.ir

DS-2CD2T22WD-I3	DS-2CD2T22WD-I5	DS-2CD2T42WD-I5	DS-2CD2T52-I5
			
"1/2.8"" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F1.4 lens (6mm optional), IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ -3: 1pcs EXIR LED, up to 30m IR range"	"1/2.8"" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F1.4 lens (6mm optional), IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ -i5: 2pcs EXIR LEDs, up to 50m IR range	"1/3"" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ -I5: 2pcs EXIR LEDs, up to 50m IR range	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F1.4 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ ,2pcs EXIR LEDs, up to 50m IR range
6,900,000 IRR	7,210,000 IRR	8,040,000 IRR	CALL
DS-2CD2942F-IS	DS-2CD2F22FWD-IS	DS-2CD2F42FWD-IS	DS-2CD2F52F-IS
			
"1/2.8"" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included),-S: Audio/alarm	"1/2.8"" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included),-S: Audio/alarm	"1/3"" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 1920x1080: 25fps(P)/ 30fps(N), 4mm/ F2.0 lens (2.8/6mm lens optional), H.264+ Optimized Codec, H.264/MJPEG, dual-stream, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to128GB (SD card not included), Pan:0° ~180°, Tilt: 0°~75°, -S: Audio/Alarm IO	"1/3"" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps,2048x1536: 25fps(P)/ 30fps(N), 4mm/ F2.0 lens (2.8/6mm lens optional), H.264+ Optimized Codec, H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, -S: Audio/Alarm IO"
16,690,000 IRR	7,590,000 IRR	8,420,000 IRR	10,430,000 IRR

DS-2CD2E20F-W	DS-2CD2Q10FD-IW	DS-2CD2D14WD
		
"1/3"" Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), Color Lens Cover optional -W: Built-in Wi-Fi"	1/4" Progressive CMOS, ICR, 0lux with IR, 4mm, Pan/tilt rotation, 1280x720:25fps(P)/30fps(N), H.264/MJPEG, dual-stream, DC5V, DWDR, 3D DNR, BLC, Support on-board card slot (SD card not included), Audio, Alarm IO, Up to 10m IR, PIR, Wi-Fi with WPS connection,	1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC,
6,460,000 IRR	6,820,000 IRR	5,340,000 IRR



تهران، خیابان یوسف آباد، خیابان شهید جهان آرا، خیابان ۳۹، پلاک ۴۰
 ۰۲۱۸۸۳۵۲۷۲۴
www.agrintech.ir - www.optix.ir





Network Video Recorder

HIKVISION

OTIX
IMAGING TECHNOLOGY



- **DS-7600 Series NVR**
- **4 ch**





Model	DS-7604NI-E1	DS-7604NI-E1/4P
Appearance		
Output Bandwidth	80Mbps	80Mbps
PoE Ports	N/A	4
Decoding Capability	4-ch 1080P	4-ch 1080P
Description	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case
Price	4,800,000 IRR	7,070,000 IRR

- **DS-7600 Series NVR**
- **8 ch**



Model	DS-7608NI-E2	DS-7608NI-E2/8P	DS-7608NI-K2
Appearance			
Output Bandwidth	80Mbps	80Mbps	160Mbps
PoE Ports	N/A	8	N/A
Decoding Capability	6-ch 1080P	6-ch 1080P	2-ch 4K / 8-ch 1080P
Description	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)
Price	6,690,000 IRR	11,170,000 IRR	8,950,000 IRR

- **DS-7600 Series NVR**




- **16 ch**

Model	DS-7616NI-E2	DS-7616NI-E2/8P	DS-7616NI-E2/16P	DS-7616NI-K2
Appearance				
Output Bandwidth	80Mbps	80Mbps	80Mbps	160Mbps
PoE Ports	N/A	8	16	N/A
Decoding Capability	6-ch 1080P	6-ch 1080P	6-ch 1080P	2-ch 4K / 8-ch 1080P
Description	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case, alarmI/O:4/1(optional)
Price	7,380,000 IRR	11,730,000 IRR	15,130,000 IRR	10,090,000 IRR

- **DS -7700 Series NVR**
- **16 ch**

Model	DS-7716NI-E4	DS-7716NI-E4/16P	DS-7716NI-K4
Appearance			
Output Bandwidth	80Mbps	80Mbps	160Mbps
PoE Ports	N/A	16	N/A
Decoding Capability	6-ch 1080P	6-ch 1080P	2-ch 4K / 8-ch 1080P
Description	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5Ucase,19"	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"
Price	14,500,000 IRR	22,320,000 IRR	17,900,000 IRR

- **DS -7700 Series NVR**
- **32 ch**

Model	DS-7732NI-E4	DS-7732NI-E4/16P	DS-7732NI-K4
Appearance			
Output Bandwidth	80Mbps	80Mbps	160Mbps
PoE Ports	N/A	16	N/A
Decoding Capability	6-ch 1080P	6-ch 1080P	2-ch 4K / 8-ch 1080P
Description	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"
Price	18,910,000 IRR	26,720,000 IRR	22,440,000 IRR

